



Technical parameter

914 mm repeat

914 mm repeat												
	screen length	mm	1780	1980	2080	2200	2380	2650	2950	3050	3200	3500
60 mesh	open area	%	19-20	19-20	19-20	19-20	19-20	19-20	19-20	19-20	19-20	19-20
	thickness	micron	113	117	123	125	125	125	125	125	125	125
	weight	gram	1150	1300	1380	1460	1580	1760	1950	2000	2150	2350
80 mesh	open area	%	17-18	17-18	17-18	17-18	17-18	17-18	17-18	17-18	17-18	17-18
	thickness	micron	110	115	120	125	125	125	125	125	125	125
	weight	gram	1150	1300	1380	1460	1580	1760	1950	2000	2150	2350
105 mesh	open area	%	15-16	15-16	15-16	15-16	15-16	15-16	15-16	15-16	15-16	15-16
	thickness	micron	105	110	115	115	125	125	125	125	125	125
	weight	gram	1150	1300	1380	1460	1580	1760	1950	2000	2150	2350
125 mesh	open area	%	14-15	14-15	14-15	14-15	14-15	14-15	14-15	14-15	14-15	14-15
	thickness	micron	102	108	115	115	120	120	120	120	120	120
	weight	gram	1140	1300	1380	1460	1580	1750	1900	2100	2130	2300
135 mesh	open area	%	13-14	13-14	13-14	13-14	13-14	13-14	13-14	13-14	13-14	13-14
	thickness	micron	110	110	115	115	120	120	120	120	120	120
	weight	gram	1120	1300	1360	1450	1550	1730	1900	2100	2120	2300
155 mesh	open area	%	12-13	12-13	12-13	12-13	12-13	12-13	12-13	12-13	12-13	12-13
	thickness	micron	105	105	105	105	110	110	110	110	110	110
	weight	gram	1120	1250	1320	1430	1500	1700	1900	2050	2100	2250

640 mm repeat

	screen length	mm	1450	1780	1980	2080	2200	2380	2650	2950	3050	3200	3500
30 mesh	open area	%	x	30-32	30-32	30-32	30-32	30-32	30-32	30-32	30-32	30-32	30-32
	thickness	micron	x	145	145	145	145	145	145	145	145	145	145
	weight	gram	x	825	920	965	1020	1100	1225	1370	1400	1470	1620
40 mesh	open area	%	x	30-32	30-32	30-32	30-32	30-32	30-32	30-32	30-32	30-32	30-32
	thickness	micron	x	145	145	145	145	145	145	145	150	150	150
	weight	gram	x	825	920	965	1020	1100	1225	1370	1420	1500	1650
60 mesh	open area	%	19-20	19-20	19-20	19-20	19-20	19-20	19-20	19-20	19-20	19	19
	thickness	micron	120	105	110	115	115	115	120	125	125	125	125
	weight	gram	650	780	890	945	990	1100	1280	1460	1500	1550	1760
80 mesh	open area	%	17-18	17-18	17-18	17-18	17-18	17-18	17-18	17-18	17-18	17-18	17-18
	thickness	micron	115	105	107	110	110	110	115	120	120	120	120
	weight	gram	640	770	860	905	950	1050	1230	1400	1450	1500	1700
105 mesh	open area	%	15-16	15-16	15-16	15-16	15-16	15-16	15-16	15-16	15-16	15	15
	thickness	micron	110	100	102	105	105	107	112	115	115	115	115
	weight	gram	635	750	860	905	950	1040	1230	1395	1450	1500	1680
125 mesh	open area	%	14-15	14-15	14-15	14-15	14-15	14-15	14	14	14	14	14
	thickness	micron	107	95	100	105	105	106	108	110	110	115	115
	weight	gram	620	740	840	870	920	1000	1200	1360	1400	1450	1630
135 mesh	open area	%	x	13-14	13-14	13-14	13-14	13-14	13-14	13-14	13-14	13-14	13-14
	thickness	micron	x	93	98	102	102	105	105	110	110	115	115
	weight	gram	x	730	830	865	920	1000	1200	1360	1400	1440	1630
155 mesh	open area	%	x	12-13	12-13	12-13	12-13	12-13	12-13	12-13	12-13	12-13	12-13
	thickness	micron	x	90	95	97	100	102	102	105	105	107	110
	weight	gram	x	700	800	845	900	980	1170	1330	1370	1430	1600
165 mesh	open area	%	x	11-12	11-12	11-12	11-12	11-12	11-12	11-12	11-12	11-12	11-12
	thickness	micron	x	90	90	93	95	100	100	105	105	107	110
	weight	gram	x	680	780	825	880	960	1155	1300	1350	1420	1580

819 mm repeat

	screen length	mm	1780	1980	2080	2200	2380	2650	2950	3050	3200	3500
60 mesh	open area	%	19-20	19-20	19-20	19-20	19-20	19-20	19-20	19-20	19-20	19-20
	thickness	micron	110	115	120	120	120	120	120	120	122	125
	weight	gram	1000	1120	1170	1240	1350	1540	1690	1750	1850	2180
80 mesh	open area	%	17-18	17-18	17-18	17-18	17-18	17-18	17-18	17-18	17-18	17-18
	thickness	micron	110	115	120	120	120	120	120	120	122	125
	weight	gram	1000	1120	1170	1240	1350	1540	1690	1750	1850	2180
105 mesh	open area	%	15-16	15-16	15-16	15-16	15-16	15-16	15-16	15-16	15-16	15-16
	thickness	micron	105	110	115	115	115	115	115	115	117	120
	weight	gram	1000	1120	1170	1240	1350	1500	1690	1750	1800	2150
125 mesh	open area	%	14-15	14-15	14-15	14-15	14-15	14-15	14-15	14-15	14-15	14-15
	thickness	micron	102	108	115	115	115	115	115	117	117	117
	weight	gram	980	1100	1150	1220	1350	1500	1690	1750	1800	2150
135 mesh	open area	%	13-14	13-14	13-14	13-14	13-14	13-14	13-14	13-14	13-14	13-14
	thickness	micron	102	103	105	105	105	110	110	110	110	110
	weight	gram	980	1100	1150	1220	1350	1500	1620	1750	1830	2100
155 mesh	open area	%	12-13	12-13	12-13	12-13	12-13	12-13	12-13	12-13	12-13	12-13
	thickness	micron	100	100	100	102	102	105	105	105	105	105
	weight	gram	970	1100	1150	1200	1330	1500	1600	1700	1800	2080