






PTFE open mesh conveyer belts



We select fine glassfiber of Kevlar as basic weaving material coated with excellent PTFE resin to make it into various PTFE open mesh conveyer belts.

Features of PTFE conveyer belts:

- High temperature resistance--it can continuously work under-140 to 260°C, maximum resistance to high temperature up to 360°C
- Permeability--it can avoid wasting heat & improve drying efficiency for it's permeability.
- Chemical resistance--it can resist all most of chemical & Dyestuff of pigment, reactive, vat, disperse etc.
- Non stick--it is easy to remove all kinds of adhesives such as resin, paint and chemical, easy to clean.

Good flex fatigue resistance --it has high tensile strength and excellent flex fatigue resistance. It's better for small wheels.

Applications:


- Dryer of rotary printing machine & flat bad printing machine for drying of all kinds of fabrics 100% cotton, polyester cotton & 100% silk, printed with any kind of dyestuff.
- Shirinking machine for garment fabric, high-frequency and UV dryer.
- Conveyer belt for hot-air dryer, various of food baking, quick-frozen machines.
- Oiling machine for paper glazing and waxing, plant engineering.
- Separating sheet for hardboard production etc.



FAISAL ENTERPRISES

502, 503 4th Floor, Business Centre, 8/8 New Civil Line, The Mall
Faisalabad-Pakistan. Tel: +92 41 2629773-4, Fax: +92 41 2629775,
E-mail: info@faisalenterprises.com
URL : www.faisalenterprises.com

PTFE OPEN MESH CONVEYER BELTS



Item no	Mesh Size	Material	Thickness	Weight	Resistance	Max Width	Tensile Strength
6001	1 x 1mm	fiberglass	0.5mm	390g/m ²	-70-260°C	4000mm	1600/1500N/5cm
6002	2 x 2mm	fiberglass	0.7mm	450g/m ²	-70-260°C	4000mm	2200/1500N/5cm
6003	4 x 4mm	fiberglass	1.0mm	500g/m ²	-70-260°C	4000mm	2100/1500N/5cm
6004	4 x 4mm	fiberglass	1.0mm	480g/m ²	-70-260°C	4000mm	2100/1500N/5cm
6007	4 x 4mm	Fiberglass +kevlar	1.2mm	560g/m ²	-70-260°C	4000mm	3300/2800N/5cm
6008	4 x 4mm	fiberglass	1.0mm	570g/m ²	-70-260°C	4000mm	2800/1580N/5cm
6010	4 x 4mm	kevlar	1.0mm	460g/m ²	-70-260°C	4000mm	3500/3300N/5cm
6012	4 x 4mm	fiberglass	1.0mm	580g/m ²	-70-260°C	4000mm	2800/1500N/5cm
6013	10 x 10mm	fiberglass	1.0mm	450g/m ²	-70-260°C	4000mm	1100/1000N/5cm
6014	0.5 x 1mm	fiberglass	0.5mm	420g/m ²	-70-260°C	4000mm	2200/1500N/5cm
6015	2 x 2.5mm	fiberglass	0.9mm	470g/m ²	-70-260°C	3000mm	2200/1500N/5cm



FAISAL ENTERPRISES

502, 503 4th Floor, Business Centre, 8/8 New Civil Line,
The Mall Faisalabad-Pakistan.

Tel: +92 41 2629773-4, Fax: +92 41 2629775

E-mail: info@faisalenterprises.com

URL : www.faisalenterprises.com